


SOLAR'S MOST TRUSTED



rec Alph α [®] pure Black Series

Product Specifications



400_{wp}
20.3_W/_{ft}²



ELIGIBLE



experience




performance



Product SPECIFICATIONS

REC ALPHA PURE BLACK SERIES Product SPECIFICATIONS



Measurements in mm [in]

GENERAL DATA

Cell type:	132 half-cut REC heterojunction cells with lead-free, gapless technology 6 strings of 22 cells in series	Connectors:	Stäubli MC4PV-KBT4/KST4 12 AWG (4 mm ²) in accordance with IEC 62852 IP68 only when connected
Glass:	0.13 in (3.2 mm) solar glass with anti-reflection surface treatment	Cable:	12 AWG (4 mm ²) PV wire, 43±47 in (1.1±1.2 m) in accordance with EN 50618
Backsheet:	Highly resistant polymer (black)	Dimensions:	71.7 x 40 x 1.2 in (1821 x 1016 x 30 mm)
Frame:	Anodized aluminum (black)	Weight:	45 lbs (20.5 kg)
Junction box:	3-part, 3 bypass diodes, IP67 rated in accordance with IEC 62790	Origin:	Made in Singapore

ELECTRICAL DATA

Product Code*: REC xxxAA Pure Black

	385	390	395	400	405
Power Output - P _{MAX} [Wp]	385	390	395	400	405
Watt Class Sorting - (W)	0/+5	0/+5	0/+5	0/+5	0/+5
Nominal Power Voltage - V _{MPP} [V]	41.2	41.5	41.8	42.1	42.4
Nominal Power Current - I _{MPP} [A]	9.35	9.40	9.45	9.51	9.56
Open Circuit Voltage - V _{OC} [V]	48.5	48.6	48.7	48.8	48.9
Short Circuit Current - I _{SC} [A]	9.99	10.03	10.07	10.10	10.14
Power Density (W/sq ft)	19.3	19.6	19.8	20.1	20.3
Panel Efficiency [%]	20.8	21.1	21.3	21.6	21.9
Power Output - P _{MAX} [Wp]	293	297	301	305	309
Nominal Power Voltage - V _{MPP} [V]	38.8	39.1	39.4	39.7	40.0
Nominal Power Current - I _{MPP} [A]	7.55	7.59	7.63	7.68	7.72
Open Circuit Voltage - V _{OC} [V]	45.7	45.8	45.9	46.0	46.1
Short Circuit Current - I _{SC} [A]	8.07	8.10	8.13	8.16	8.19

Values at standard test conditions (STC: air mass AM 1.5, irradiance 1075 W/sq ft (1000 W/m²), temperature 77°F (25°C), based on a production spread with a tolerance of P_{MAX}, V_{OC} & I_{SC} ±3% within one watt class. Nominal module operating temperature (NMOT: air mass AM 1.5, irradiance 800 W/m², temperature 68°F (20°C), wind speed 3.3 ft/s (1 m/s). * Where xxx indicates the nominal power class [P_{MAX}] at STC above.

CERTIFICATIONS

IEC 61215:2016, IEC 61730:2016, UL 61730 (Pending)
ISO 14001:2004, ISO 9001:2015, OHSAS 18001:2007, IEC 62941



WARRANTY

	Standard	REC ProTrust	
Installed by an REC Certified Solar Professional	No	Yes	Yes
System Size	All	≤25 kW	25-500 kW
Product Warranty (yrs)	20	25	25
Power Warranty (yrs)	25	25	25
Labor Warranty (yrs)	0	25	10
Power in Year 1	98%	98%	98%
Annual Degradation	0.25%	0.25%	0.25%
Power in Year 25	92%	92%	92%

See warranty documents for details. Conditions apply

MAXIMUM RATINGS

Operational temperature:	-40 ... +185°F (-40 ... +85°C)
Maximum system voltage:	1000 V
Maximum test load (Front):	+7000 Pa (146 lbs/sq ft)*
Maximum test load (Rear):	-4000 Pa (83.5 lbs/sq ft)*
Max series Fuse rating:	25 A
Max reverse current:	25 A

* See installation manual for mounting instructions.
Design load = Test load / 1.5 (safety factor)


TEMPERATURE RATINGS

Nominal Module Operating Temperature:	44°C (±2°C)
Temperature coefficient of P _{MAX} :	-0.26 %/°C
Temperature coefficient of V _{OC} :	-0.24 %/°C
Temperature coefficient of I _{SC} :	0.04 %/°C

*The temperature coefficients stated are linear values

LOW LIGHT BEHAVIOUR

Typical low irradiance performance of module at STC:



Specifications subject to change without notice.

Ref: PM-DS-12-01-Rev-A-03/21

Founded in 1996, REC Group is an international pioneering solar energy company dedicated to empowering consumers with clean, affordable solar power. As Solar's Most Trusted, REC is committed to high quality, innovation, and a low carbon footprint in the solar materials and solar panels it manufactures. Headquartered in Norway with operational headquarters in Singapore, REC also has regional hubs in North America, Europe, and Asia-Pacific.

