



Hybrid Inverter 4-12kW

MHT-4/5/6/8/10/12K-25

15A

Max. PV Input Current

110%

Unbalanced Output

25A

Max. Charge/Discharge

Residential | Three Phase | HV Battery | 2 MPPTs



Maximized Energy Harvesting

- 160% DCoversizing boostssolar capture
- 110% unbalanced output enhances self-consumption
- Continuous 110% AC overloading sustains power
- Smooth transition to backup power ensures continuity during power outages



Engineered for Versatility

- Wide 135-750V rangefits diversebatteries
- Up to 200% max backup @10s handles overloads
- IP65 protects both indoors and outdoors
- Silent 25dB operation for comfort



Intelligent Energy Dynamics

- 7workmodes for diverseuse
- Supports both ToU and dynamic pricing strategies for optimized energy use and cost savings
- Centralized smart management for efficiency



Simplified Interaction

- Remote upgrades maintainsystemhealth
- Solinteg I-light for quick status checks
- OLED and App for easy control



Integ M Series

The Power Master



Hybrid Inverter 4-12kW

Models		MHT-4K-25	MHT-5K-25	MHT-6K-25	MHT-8K-25	MHT-10K-25	M H T-12 K-2 5
PV Side							
Max. PV Array Power	[kWp]	6.4	8	9.6	10.4	16	19.2
Max. PV Input Voltage *	[V]	1000*					
Rated PV Input Voltage	[V]	620					
Start-up Voltage	[V]	135					
MPPT Operating Voltage Range *	[V]	120-950*	120-950*	120-950*	200-950*	200-950*	200-950*
No. of MPP Trackers		2	2	2	2	2	2
No. of Strings per MPPT		1/1	1/1	1/1	1/1	1/1	1/1
Max. Input Current per MPPT	[A]	15/15	15/15	15/15	15/15	15/15	15 / 15
Max. Short-circuit Current per MPPT	[A]	20/20	20/20	20/20	20/20	20/20	20/20
Battery Side							
Battery Type		Litnum-lion					
Battery Voltage Range	[V]	135-750					
No. of Battery Input		1					
Max. Charging/Discharge Current	[A]	25/25					
Max. Charging/Discharge Power	[W]	4/4	5/5	6/6	8/8	10/10	12 / 12
Grid Side (On-Grid)							
Rated Output Power	[kW]	4	5	6	8	10	12
Max. Output Apparent Power	[kVA]	4.4	5.5	6.6	8.8	11(1)	13.2
Rated AC Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V					
Rated AC Frequency	[Hz]	50/60					
Rated Output Current	[A]	6.1/5.8/5.6	7.6/7.2/6.9	9.1/8.7/8.3	12.1/11.6/11.1	15.2/14.5/13.9	18.2/17.4/16.7
Max. Output Current	[A]	6.7	8.3	10.0	13.3	16.5(2)	20.0
Power Factor		0.8 leading ...0.8 lagging					
THDi (@Rated Power)		<3%					
Max. Input Apparent Power **	[kVA]	8.0	10.0	12.0	16.0	16.5	16.5
Rated AC Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V					
Rated AC Frequency	[Hz]	50/60					
Max. AC Input Current	[A]	12.2	15.2	18.2	24.4	25.0	25.0
Back-up Side (Off-Grid)							
Rated Output Power	[kW]	4	5	6	8	10	12
Peak Output Apparent Power	[kVA]	9@10s	9@10s	9@10s	18@10s	18@10s	18 @10 s
Rated Output Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V					
Rated Output Frequency	[Hz]	50/60					
Rated Output Current	[A]	6.1/5.8/5.6	7.6/7.2/6.9	9.1/8.7/8.3	12.1/11.6/11.1	15.2/14.5/13.9	18.2/17.4/16.7
On/Off-grid Switching Time	[ms]	< 10ms					
THDv (@Linear Load)		<3%					
Efficiency							
MPPT Efficiency		99.90	99.90	99.90	99.90	99.90	99.90
Max. Efficiency		%	%	%	%	%	%
European Efficiency		98.10	98.10	98.10	98.20	98.20	98.20
Protection							
Integrated Protection		97.30	97.30	97.30	97.40	97.40	97.40
	%	DC reverse polarity protection / Battery input reverse connection protection / Insulation resistance protection / Surge protection / DC/AC: Type II / Type I / Over-temperature protection / Residual current protection / Islanding protection / AC over-voltage protection / Overload protection / AC short-circuit protection					%
General Data							
Dimensions	[W×H×D mm]	534×418×210					
Weight	[KG]	26					
Ingress Protection		IP65					
Standby Self-consumption	[W]	< 15					
Topology		Transformerless					
Operating Temperature Range	[°C]	-30~60					
Relative Humidity	[%]	0~100					
Max. Operation Altitude	[m]	3000					
Over Voltage Category		II(PV+Battery), III(Mains)					
Cooling		Natural Convection					
Noise Level		<25					
Display	[dB]	LED & OLED					
Communication		CAN, RS485					

* PV Max. input voltage is 950V without battery, or 850V with battery, otherwise inverter will be waiting;

** Max apparent power from the grid means the maximum power imported from the utility grid used to satisfy the backup loads and charge the battery;

(1) G98: 10.5kVA; (2) G98: 16.00A;

